



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-19A
	4
	480 L/min.
	350 bar
	0,7 cc/min.
	15 L/min.
	0,25 - 0,33 L/min.
	2 ms
-	5
	41,3 mm
	474 - 508 Nm
	4 mm
	15 mm
	9 - 10 Nm
	1.43 kg.
Seal kit - Cartridge	Buna: 990-219-007
Seal kit - Cartridge	Viton: 990-219-006
Seal kit - Cartridge	Buna: 990-219-007
Seal kit - Cartridge	Viton: 990-219-006

# OPTION SELECTION EXAMPLE: RSJSLAN

	(L)	(A)	(N)	MATERIAL/COATING
<b>L</b>	-	<b>A</b> 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	<b>N</b>	Standard Material/Coating
<b>C</b>	-	<b>B</b> 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	<b>V</b>	/AP
<b>K</b>	-	<b>C</b> 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)		/LH
		<b>N</b> 60 - 800 psi (4 - 55 bar), 400 psi (28 bar)		
		<b>Q</b> 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)		
		<b>W</b> 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)		

## TECHNICAL FEATURES

- 3
- 3                    1
- 150
- 3                    1:1                    3                    5000 psi 350 bar
- 
- 2
- Sun                    /

## PERFORMANCE CURVES

