



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-163A
	0
	30 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min.@70 bar
	15 L/min.
	0,11 - 0,16 L/min.
	10 ms
-	5
	19,1 mm
	27 - 33 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.11 kg.
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	EPDM: 990-163-014
Seal kit - Cartridge	Polyurethane: 990-163-002
Seal kit - Cartridge	Viton: 990-163-006
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	EPDM: 990-163-014
Seal kit - Cartridge	Polyurethane: 990-163-002
Seal kit - Cartridge	Viton: 990-163-006

OPTION SELECTION EXAMPLE: RVBALAN

	(L)	(A)	(N)	MATERIAL/COATING
L	A	75 - 3000 psi (5 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
	B	75 - 1500 psi (5 - 105 bar), 1000 psi (70 bar)	E	/AP
	C	75 - 6000 psi (5 - 420 bar), 1000 psi (70 bar)	V	
	N	75 - 800 psi (5 - 55 bar), 400 psi (28 bar)		
	Q	75 - 400 psi (5 - 28 bar), 200 psi (14 bar)		
	W	75 - 4500 psi (5 - 315 bar), 1000 psi (70 bar)		

TECHNICAL FEATURES

- 3
- 2
- 75 psi (5 bar)
- 2 1:1
- EPDM
- Sun /

PERFORMANCE CURVES

