



CONFIGURATION

L	
A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)
N	Material/Coating

1

TECHNICAL DATA

NOTE:

	T-11A	DATA
	1	MAY
	60 L/min.	VARY
	350 bar	BY
110 SUS (24 cSt)	30 cc/min. @70 bar	
	15 L/min.	
	0,11 - 0,16 L/min.	
	10 ms	
-	5	
	22,2 mm	
	41 - 47 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	0.16 kg.	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	EPDM: 990-011-014	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	

: • O 1 0.75 in. (19 mm)

CONFIGURATION. SEE CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: RVCALAN

	(L)	(A)	(N)	MATERIAL/COATING	(/LH)
L	A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	/LH	-
C	-	B	E	/AP	-
		50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	EPDM		Standard Material/Coating
		C	V		
		150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)			
		D			
		25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)			
		E			
		25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)			
		W			
		150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)			

TECHNICAL FEATURES

- 3
- 2
- 150
-
- 2 1:1
- EPDM
- Sun /

PERFORMANCE CURVES

