



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-11A
	1
	60 L/min.
	350 bar
110 SUS (24 cSt)	30 cc/min. @70 bar
	15 L/min.
	0,11 - 0,16 L/min.
	10 ms
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.16 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

: • 0 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: RVCALAN

	(L)	(A)	(N)	MATERIAL/COATING
L		A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
C	-		E EPDM	/AP
K		B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	V	/LH
O		C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)		
		D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)		
		E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)		
		W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)		

TECHNICAL FEATURES

- 3
- 2
- 150
-
- 2 1:1
- EPDM
- Sun /

PERFORMANCE CURVES

