



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at 110 SUS (24 cSt)	80 cc/min.@210 bar
Response Time - Typical	50 ms
Adjustment - No. of CW Turns from Min. to Max. setting	3.5
Locknut Hex Size	11,1 mm
Locknut Torque	5 - 6 Nm
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006
U.S. Patent #	10,570,932
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

CONFIGURATION OPTIONS

Model Code Example: RVCMLJN

CONTROL	(L)	ADJUSTMENT RANGE	(J)	SEAL MATERIAL	(N)	BOBINA
L Standard Screw Adjustment		J 300 - 5000 psi (20 - 350 bar), 1000 psi (70 bar) Standard Setting		N Buna-N E EPDM V Viton		No coil