



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-11A
	1
	60 L/min.
	350 bar
	0,7 cc/min.
	15 L/min.
	0,11 - 0,16 L/min.
	2 ms
	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0,15 kg
Seal kit - Cartridge	Buna: 990-611-007
Seal kit - Cartridge	Viton: 990-611-006

## OPTION SELECTION EXAMPLE: RVCSLANV

	(L)	(A)	(V)	MATERIAL/COATING
<b>L</b>	-	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	V	Standard Material/Coating
<b>C</b>	-	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	E EPDM	/AP
		C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)	N	/LH -
		N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar)		
		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)		
		W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)		

### TECHNICAL FEATURES

- 
- EPDM
- 2
- 3
- 
- 150
- 
- 2 1:1
- Sun /

### PERFORMANCE CURVES

