



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-2A
	2
	120 L/min.
	350 bar
110 SUS (24 cSt)	50 cc/min.@70 bar
	15 L/min.
	0,16 - 0,25 L/min.
	10 ms
-	5
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.29 kg.
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

: • 0 1 0.75 in. (19 mm)

OPTION SELECTION EXAMPLE: RVEALAN

	(L)	(A)	(N)	MATERIAL/COATING
L		A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	Standard Material/Coating
O			E EPDM	/AP
W		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)	V	/LH

TECHNICAL FEATURES

- 3
- 2
- 150
-
- 2 1:1
- EPDM
- Sun /

PERFORMANCE CURVES

