



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-22A
Series	2
Capacity	120 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,16 - 0,25 L/min.
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at 110 SUS (24 cSt)	50 cc/min.@70 bar
Response Time - Typical	10 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.35 kg.
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

OPTION SELECTION EXAMPLE: RVEDLAN

CONTROL

- L** Standard Screw Adjustment
- C** Tamper Resistant - Factory Set
- K** manilla

(L) ADJUSTMENT RANGE

- A** 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting
- B** 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting
- D** 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting
- E** 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting
- W** 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting

(A) SEAL MATERIAL

- N** Buna-N
- E** EPDM
- V** Viton

(N)

PERFORMANCE CURVES

