





CONFIGURATION

L	
A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)
N	
	Material/Coating

1

TECHNICAL DATA

NOTE:

	T-2A	DATA
	2	MAY
	95 L/min.	VARY
	350 bar	BY
	0,7 cc/min.	
	15 L/min.	
	0,25 - 0,33 L/min.	
	2 ms	
-	5	
	28,6 mm	
	61 - 68 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	0.29 kg.	
Seal kit - Cartridge	Buna: 990-402-007	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-402-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: RVESLAN

	(L)	(A)	(N)	MATERIAL/COATING	(/LH)
L					
C	-	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N	/LH	-
		B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	E EPDM	/AP	
		C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)	V	Standard Material/Coating	
		N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar)			
		Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)			
		W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)			

TECHNICAL FEATURES

-
- 3
- 2
- 3
-
- 150
- 2 1:1
- Sun /

PERFORMANCE CURVES

