



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Control Pilot Flow	0,16 - 0,41 L/min.
Factory Pressure Settings Established at	15 L/min.
Pressure Ramp Up Time	200 - 400 ms
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	4.5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-402-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-402-006
U.S. Patent #	6,039,070
Seal kit - Cartridge	Buna: 990-402-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-402-006

CONFIGURATION OPTIONS

Model Code Example: RVETLACN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)
L Standard Screw Adjustment		A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting		N Buna-N	
C Tamper Resistant - Factory Set		B 500 - 1500 psi (35 - 105 bar), 1000 psi (70 bar) Standard Setting		V Viton	
		C 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) Standard Setting			
		W 1000 - 4500 psi (70 - 315 bar), 1000 psi (70 bar) Standard Setting			