



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-2A
Series	2
Capacity	120 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,16 - 0,41 L/min.
Factory Pressure Settings Established at	15 L/min.
Pressure Ramp Up Time	200 - 400 ms
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	4,5
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-402-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-402-006
U.S. Patent #	6,039,070
Seal kit - Cartridge	Buna: 990-402-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-402-006

OPTION SELECTION EXAMPLE: RVETLACN

CONTROL

- L** Standard Screw Adjustment
- C** Tamper Resistant - Factory Set

(L) ADJUSTMENT RANGE

- A** 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting
- B** 500 - 1500 psi (35 - 105 bar), 1000 psi (70 bar) Standard Setting
- C** 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) Standard Setting
- W** 1000 - 4500 psi (70 - 315 bar), 1000 psi (70 bar) Standard Setting

(A) SEAL MATERIAL

- N** Buna-N
- V** Viton

(N)

PERFORMANCE CURVES

