



**CONFIGURATION**

1

<b>L</b>	
<b>A</b>	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)
<b>N</b>	
	Material/Coating

**TECHNICAL DATA**

NOTE:

	T-17A	DATA
	3	MAY
	240 L/min.	VARY
	350 bar	BY
110 SUS (24 cSt)	65 cc/min.@70 bar	
	15 L/min.	
	0,25 - 0,33 L/min.	
	10 ms	
-	5	
	31,8 mm	
	203 - 217 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	0.62 kg.	
Seal kit - Cartridge	Buna: 990-017-007	
Seal kit - Cartridge	EPDM: 990-017-014	
Seal kit - Cartridge	Polyurethane: 990-017-002	
Seal kit - Cartridge	Viton: 990-017-006	

CONFIGURATION. SEE CONFIGURATION SECTION.

# OPTION SELECTION EXAMPLE: RVGALAN

	(L)	(A)	(N)	MATERIAL/COATING	(/LH)
<b>L</b>	<b>A</b>	<b>100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)</b>	<b>N</b>	<b>/LH</b>	<b>-</b>
<b>C</b>	<b>-</b>	<b>E</b>	<b>EPDM</b>	<b>/AP</b>	<b>Standard Material/Coating</b>
		<b>B</b>			
		<b>50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)</b>			
		<b>C</b>			
		<b>150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)</b>			
		<b>D</b>			
		<b>25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)</b>			
		<b>E</b>			
		<b>25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)</b>			
		<b>J</b>			
		<b>25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar)</b>			
		<b>K</b>			
		<b>75 - 1500 psi (5 - 105 bar), 1000 psi (70 bar)</b>			
		<b>W</b>			
		<b>150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)</b>			

## TECHNICAL FEATURES

- 3
- 2
- 150
- 
- 2 1:1
- EPDM
- Sun /

## PERFORMANCE CURVES

