



### CONFIGURATION

L	Control	Standard Screw Adjustment
C	Adjustment Range	100 - 6000 psi (7 - 420 bar), 1000 psi (70 bar) Standard Setting
N	Seal Material	Buna-N
	Material/Coating	

### TECHNICAL DATA

Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at 110 SUS (24 cSt)	65 cc/min.@70 bar
Response Time - Typical	10 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

### CONFIGURATION OPTIONS

#### Model Code Example: RVGBLCN

CONTROL	(L)	ADJUSTMENT RANGE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
L	Standard Screw Adjustment	C	100 - 6000 psi (7 - 420 bar), 1000 psi (70 bar) Standard Setting	N	Buna-N	Standard Material/Coating
C	Tamper Resistant - Factory Set	A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	V	Viton	/AP Stainless Steel, Passivated
K	manilla	B	150 - 1500 psi (10,5 - 105 bar), 1000 psi (70 bar) Standard Setting			