



CONFIGURATION

L Control	Standard Screw Adjustment
C Adjustment Range	100 - 6000 psi (7 - 420 bar), 1000 psi (70 bar) Standard Setting
N Seal Material	Buna-N
Material/Coating	

TECHNICAL DATA

NOTE:

		DATA
cavidad	T-17A	MAY
Series	3	VAR
Capacity	160 L/min.	BY
Maximum Operating Pressure	350 bar	
Factory Pressure Settings Established at	15 L/min.	
Maximum Valve Leakage at 110 SUS (24 cSt)	65 cc/min.@70 bar	
Response Time - Typical	10 ms	
Adjustment - No. of CW Turns from Min. to Max. setting	5	
Valve Hex Size	31,8 mm	
Valve Installation Torque	203 - 217 Nm	
Adjustment Screw Internal Hex Size	4 mm	
Locknut Hex Size	15 mm	
Locknut Torque	9 - 10 Nm	
Model Weight	0.62 kg.	
Seal kit - Cartridge	Buna: 990-017-007	
Seal kit - Cartridge	Polyurethane: 990-017-002	
Seal kit - Cartridge	Viton: 990-017-006	
Seal kit - Cartridge	Buna: 990-017-007	
Seal kit - Cartridge	Polyurethane: 990-017-002	
Seal kit - Cartridge	Viton: 990-017-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: RVGBLCN

CONTROL	(L)	ADJUSTMENT RANGE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment		C 100 - 6000 psi (7 - 420 bar), 1000 psi (70 bar) Standard Setting		N Buna-N		Standard Material/Coating
		B 150 - 1500 psi (10,5 - 105 bar), 1000 psi (70 bar) Standard Setting		V Viton		/AP Stainless Steel, Passivated