



CONFIGURATION

L	
C	100 - 6000 psi (7 - 420 bar), 1000 psi (70 bar)
N	
	Material/Coating

TECHNICAL DATA

NOTE:
DATA
MAY
VARY
BY

	T-17A
	3
	160 L/min.
	350 bar
110 SUS (24 cSt)	65 cc/min.@70 bar
	15 L/min.
	10 ms
-	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.62 kg.
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: RVGBLCN

(L)	(C)	(N)	MATERIAL/COATING
L	C 100 - 6000 psi (7 - 420 bar), 1000 psi (70 bar) B 150 - 1500 psi (10,5 - 105 bar), 1000 psi (70 bar)	N V	Standard Material/Coating /AP

TECHNICAL FEATURES

- 120 psi (8 bar)
- X Y