



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-17A
	3
	200 L/min.
	350 bar
	0,7 cc/min.
	15 L/min.
	0,25 - 0,33 L/min.
	2 ms
-	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.63 kg.
Seal kit - Cartridge	Buna: 990-217-007
Seal kit - Cartridge	Polyurethane: 990-217-002
Seal kit - Cartridge	Viton: 990-217-006
Seal kit - Cartridge	Buna: 990-217-007
Seal kit - Cartridge	Polyurethane: 990-217-002
Seal kit - Cartridge	Viton: 990-217-006

# OPTION SELECTION EXAMPLE: RVGSLAN

	(L)	(A)	(N)	MATERIAL/COATING
<b>L</b>	<b>A</b>	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	<b>N</b>	Standard Material/Coating
			<b>E</b> EPDM <b>V</b>	/AP /LH -

## TECHNICAL FEATURES

- 
- 3
- EPDM
- 2
- 3
- 
- 150
- 2 1:1
- Sun /

## PERFORMANCE CURVES

