



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-19A
	4
	480 L/min.
	350 bar
110 SUS (24 cSt)	80 cc/min. @70 bar
	15 L/min.
	0,25 - 0,33 L/min.
	10 ms
-	5
	41,3 mm
	474 - 508 Nm
	4 mm
	15 mm
	9 - 10 Nm
	1.43 kg.
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	EPDM: 990-019-014
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	EPDM: 990-019-014
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006

OPTION SELECTION EXAMPLE: RVIALAN

(L)	(A)	(N)	MATERIAL/COATING
L	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N E EPDM V	Standard Material/Coating /AP /LH -

TECHNICAL FEATURES

- 3
- 2
- 150
-
-
- 2 1:1
- EPDM
- Sun /

PERFORMANCE CURVES

