





CONFIGURATION

L	
A	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)
N	
Material/Coating	

1

TECHNICAL DATA

NOTE:

	T-19A	DATA
	4	MAY
	480 L/min.	VARY
	350 bar	BY
	0,7 cc/min.	
	15 L/min.	
	0,25 - 0,33 L/min.	
	2 ms	
-	5	
	41,3 mm	
	474 - 508 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	1.43 kg.	
Seal kit - Cartridge	Buna: 990-219-007	
Seal kit - Cartridge	Viton: 990-219-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: RVISLAN

(L)		(A)	(N)	MATERIAL/COATING	(/LH)
L		A	N		
C		100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	V		
		B	/AP		
		50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	Standard Material/Coating		
		C			
		150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)			
		N			
		60 - 800 psi (4 - 55 bar), 400 psi (28 bar)			
		Q			
		60 - 400 psi (4 - 28 bar), 200 psi (14 bar)			
		W			
		150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)			

TECHNICAL FEATURES

-
- 3
- 2
- 3
-
- 150
- 2 1:1
- Sun /

PERFORMANCE CURVES

