



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Control Pilot Flow	0,25 - 0,33 L/min.
Factory Pressure Settings Established at	15 L/min.
Pressure Ramp Up Time	400 - 850 ms
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-219-007
Seal kit - Cartridge	Viton: 990-219-006
Seal kit - Cartridge	Buna: 990-219-007
Seal kit - Cartridge	Viton: 990-219-006

CONFIGURATION OPTIONS

Model Code Example: RVITLAN

CONTROL	(L)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment		A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting		N Buna-N		Standard Material/Coating
		C 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) Standard Setting		V Viton		IAP Stainless Steel, Passivated
		W 1000 - 4500 psi (70 - 315 bar), 1000 psi (70 bar) Standard Setting				