



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-11A
	1
	60 L/min.
	350 bar
	2,8 bar
	0,7 cc/min.
	30 cc/min.
	2 ms
-	5
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.20 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

OPTION SELECTION EXAMPLE: SCCALAN

	(L)	(A)	(N)	MATERIAL/COATING
L	A	N	Standard Material/Coating	
C -	A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar)	E EPDM	/AP	
	C 2000 - 6000 psi (140 - 420 bar), 2000 psi (140 bar)	V	/LH -	
	W 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar)			

TECHNICAL FEATURES

- 3
- 3
- 3 1:1 3 5000 psi 350 bar
- EPDM
- /AP
- Sun /

PERFORMANCE CURVES

