



Atmospherically referenced, direct-acting sequence valves with reverse-flow check will supply a secondary circuit with flow once the pressure at the inlet (port 1) has exceeded the valve setting. Additionally, these valves incorporate an integral check valve to provide reverse flow from port 2 (sequence) to port 1 (inlet). The pressure setting of this sequence valve controls the pressure at port 1 relative to the atmospheric vent.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-5A
Series	2
Capacity	30 gpm
Maximum Operating Pressure	5000 psi
Check Cracking Pressure	25 psi
Factory Pressure Settings Established at	2 in ³ /min.
Maximum Valve Leakage at Reseat	10 drops/min.
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	1 1/8 in.
Valve Installation Torque	45 - 50 lbf ft
Adjustment Screw Internal Hex Size	5/32 in.
Locknut Hex Size	9/16 in.
Locknut Torque	80 - 90 lbf in.
Model Weight	0.81 lb.
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	Viton: 990-203-006

OPTION SELECTION EXAMPLE: SCEBLAN

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
L Standard Screw Adjustment	A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N	
C Tamper Resistant - Factory Set	C 2000 - 6000 psi (140 - 420 bar), 2000 psi (140 bar) Standard Setting	V Viton	
K Handknob	D 200 - 800 psi (14 - 55 bar), 400 psi (28 bar) Standard Setting		
	E 100 - 400 psi (7 - 28 bar), 200 psi (14 bar) Standard Setting		
	W 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting		

TECHNICAL FEATURES

- Suitable for use in load holding applications.
- Atmospherically referenced valves should only be used where it is impossible have a drain connection. Over time, the atmospherically referenced valves may leak externally or allow moisture into the spring chamber.
- Approximately 1 drop (0,07 cc) of fluid will pass into the vented spring chamber every 4000 cycles.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

