



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-17A
	3
	240 L/min.
	350 bar
	1,7 bar
	0,7 cc/min.
	30 cc/min.
	2 ms
-	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.72 kg.
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

# OPTION SELECTION EXAMPLE: SCGALAN

	(L)	(A)	(N)	MATERIAL/COATING
<b>L</b>	<b>A</b>	<b>N</b>	<b>V</b>	Standard Material/Coating
	500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar)			/AP
	B 300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar)			/LH -
	C 2000 - 6000 psi (140 - 420 bar), 2000 psi (140 bar)			
	D 200 - 800 psi (14 - 55 bar), 400 psi (28 bar)			
	E 100 - 400 psi (7 - 28 bar), 200 psi (14 bar)			
	W 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar)			

## TECHNICAL FEATURES

- 3
- 3
- 3      1:1      3      5000 psi 350 bar
- 
- Sun      /

## PERFORMANCE CURVES

