



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-19A
	4
	480 L/min.
	350 bar
	1,7 bar
	0,7 cc/min.
	30 cc/min.
	2 ms
-	5
	41,3 mm
	474 - 508 Nm
	4 mm
	15 mm
	9 - 10 Nm
	1.67 kg.
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	EPDM: 990-019-014
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	EPDM: 990-019-014
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006

OPTION SELECTION EXAMPLE: SCIALAN

	(L)	(A)	(N)	MATERIAL/COATING
L	A	N	Standard Material/Coating	/AP
	500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar)	EPDM V		
	300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar)			
	2000 - 6000 psi (140 - 420 bar), 2000 psi (140 bar)			
	200 - 800 psi (14 - 55 bar), 400 psi (28 bar)			
	100 - 400 psi (7 - 28 bar), 200 psi (14 bar)			
	800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar)			

TECHNICAL FEATURES

- 3
- 3
- 3 1:1 3 5000 psi 350 bar
-
- EPDM
- Sun /

PERFORMANCE CURVES

