



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-2A
Series	2
Capacity	120 L/min.
Maximum Operating Pressure	350 bar
Control Pilot Flow	0,16 - 0,41 L/min.
Factory Pressure Settings Established at	15 L/min.
Pressure Ramp Up Time	200 - 400 ms
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	4.5
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-402-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-402-006

OPTION SELECTION EXAMPLE: SDFTLAN

CONTROL

(L) ADJUSTMENT RANGE

(A) SEAL MATERIAL

(N)

L Standard Screw Adjustment

A 2000 - 3000 psi (140 - 210 bar), 2000 psi (140 bar) Standard Setting

C 4500 - 6000 psi (315 - 420 bar), 4500 psi (315 bar) Standard Setting

W 3000 - 4500 psi (210 - 315 bar), 3000 psi (210 bar) Standard Setting

N Buna-N

V Viton

PERFORMANCE CURVES

