



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-17A
Series	3
Capacity	240 L/min.
Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at Reseat	0,7 cc/min.
Pressure Ramp Up Time	300 - 500 ms
Response Time - Typical	2 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Adjustment Screw Internal Hex Size	4 mm
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Model Weight	0.85 kg.
Seal kit - Cartridge	Buna: 990-217-007
Seal kit - Cartridge	Polyurethane: 990-217-002
Seal kit - Cartridge	Viton: 990-217-006
Seal kit - Cartridge	Buna: 990-217-007
Seal kit - Cartridge	Polyurethane: 990-217-002
Seal kit - Cartridge	Viton: 990-217-006

OPTION SELECTION EXAMPLE: SDHTLAN

CONTROL

- L** Standard Screw Adjustment
- C** Tamper Resistant - Factory Set

(L) ADJUSTMENT RANGE

- A** 2000 - 3000 psi (140 - 210 bar), 2000 psi (140 bar) Standard Setting
- C** 4500 - 6000 psi (315 - 420 bar), 4500 psi (315 bar) Standard Setting
- W** 3000 - 4500 psi (210 - 315 bar), 3000 psi (210 bar) Standard Setting

(A) SEAL MATERIAL

- N** Buna-N
- V** Viton

(N)

PERFORMANCE CURVES

