



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-17A
	3
	240 L/min.
	350 bar
	300 - 500 ms
	0,7 cc/min.
	15 L/min.
	2 ms
	5
	31,8 mm
	203 - 217 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.85 kg.
Seal kit - Cartridge	Buna: 990-217-007
Seal kit - Cartridge	Polyurethane: 990-217-002
Seal kit - Cartridge	Viton: 990-217-006
Seal kit - Cartridge	Buna: 990-217-007
Seal kit - Cartridge	Polyurethane: 990-217-002
Seal kit - Cartridge	Viton: 990-217-006

# OPTION SELECTION EXAMPLE: SDHTLAN

(L)

(A)

(N)

<b>L</b>	<b>A</b>	<b>N</b>
	2000 - 3000 psi (140 - 210 bar), 2000 psi (140 bar)	V
	C 4500 - 6000 psi (315 - 420 bar), 4500 psi (315 bar)	
	W 3000 - 4500 psi (210 - 315 bar), 3000 psi (210 bar)	

## TECHNICAL FEATURES

- 
- 3 1
- 
- 3 1:1 3 5000 psi 350 bar
- 2
- 2
- 
- 
- 1 2
- 
- Sun /

## PERFORMANCE CURVES

