



## CONFIGURATION

<b>F</b> Control	Hex Head Screw with Locknut
<b>A</b> Adjustment Range	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting
<b>N</b> Seal Material	Buna-N
	Material/Coating

## TECHNICAL DATA

NOTE:

		DATA
cavidad	T-11A	MAY
Series	1	VARY
Capacity	60 L/min.	BY
Maximum Operating Pressure	350 bar	
Factory Pressure Settings Established at	Kick down point	
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.	
Response Time - Typical	25 ms	
Adjustment - No. of CW Turns from Min. to Max. setting	5	
Valve Hex Size	22,2 mm	
Valve Installation Torque	41 - 47 Nm	
Adjustment Screw Internal Hex Size	4 mm	
Locknut Hex Size	15 mm	
Locknut Torque	9 - 10 Nm	
Model Weight	0.14 kg.	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	

CONFIGURATION. SEE  
CONFIGURATION SECTION.

## OPTION SELECTION EXAMPLE: SQDBFAN

CONTROL	(F)	ADJUSTMENT RANGE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>F</b> Hex Head Screw with Locknut	<b>A</b>	100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b>	Buna-N		Standard Material/Coating
<b>C</b> Tamper Resistant - Factory Set	<b>B</b>	50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting	<b>V</b>	Viton	<b>/AP</b>	Stainless Steel, Passivated
<b>J</b> Capped Screw Adjustment	<b>D</b>	25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting				
<b>K</b> manilla	<b>E</b>	25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting				
<b>L</b> Standard Screw Adjustment	<b>W</b>	150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting				

### PERFORMANCE CURVES

