



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	Kick down point
Maximum Valve Leakage at 110 SUS (24 cSt)	65 cc/min.
Response Time - Typical	25 ms
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

CONFIGURATION OPTIONS

Model Code Example: SQHBLAN

CONTROL

(L)

ADJUSTMENT RANGE

(A)

SEAL MATERIAL

(N)

- L** Standard Screw Adjustment
- C** Tamper Resistant - Factory Set
- K** manilla

- A** 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)
Standard Setting
- B** 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)
Standard Setting
- D** 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)
Standard Setting
- E** 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)
Standard Setting
- W** 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)
Standard Setting

- N** Buna-N
- V** Viton