



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| | T-11A |
| | 1 |
| | 60 L/min. |
| | 350 bar |
| | 0,7 cc/min. |
| | 30 cc/min. |
| | 2 ms |
| - | 4 |
| | 22,2 mm |
| | 41 - 47 Nm |
| | 4 mm |
| | 15 mm |
| | 9 - 10 Nm |
| | 0.20 kg. |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |

OPTION SELECTION EXAMPLE: SXCALAN

| | (L) | (A) | (N) | MATERIAL/COATING |
|----------|--|----------|----------|---------------------------|
| L | A | V | N | Standard Material/Coating |
| | 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) | | | /AP |
| | 300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar) | | | /LH - |
| | 2000 - 6000 psi (140 - 420 bar), 2000 psi (140 bar) | | | |
| | 200 - 800 psi (14 - 55 bar), 400 psi (28 bar) | | | |
| | 100 - 400 psi (7 - 28 bar), 200 psi (14 bar) | | | |
| | 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) | | | |

TECHNICAL FEATURES

- 3
- 3
- 3 1:1 3 5000 psi 350 bar
-
- /AP
- Sun /

PERFORMANCE CURVES

