



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------------|---------------------------|
| cavidad | T-8A |
| Series | P |
| Maximum Operating Pressure | 350 bar |
| Port Configuration | 2 Port |
| Valve Hex Size | 22,2 mm |
| Valve Installation Torque | 27 - 33 Nm |
| Seal kit - Cartridge | Buna: 990-008-007 |
| Seal kit - Cartridge | EPDM: 990-008-014 |
| Seal kit - Cartridge | Polyurethane: 990-008-002 |
| Seal kit - Cartridge | Viton: 990-008-006 |
| Seal kit - Cartridge | Buna: 990-008-007 |
| Seal kit - Cartridge | EPDM: 990-008-014 |
| Seal kit - Cartridge | Polyurethane: 990-008-002 |
| Seal kit - Cartridge | Viton: 990-008-006 |

OPTION SELECTION EXAMPLE: XACAXXN

| CONTROL | (X) | ADJUSTMENT RANGE | (X) | SEAL MATERIAL | (N) | MATERIAL/COATING | |
|---------|-----|------------------------------|-----|---------------|-----|------------------|-----------------------------|
| X | | todos los puertos bloqueados | X | - | N | Buna-N | Standard Material/Coating |
| | | | | E | | EPDM | /AP |
| | | | | V | | Viton | Stainless Steel, Passivated |