



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	34 L/min.

OPTION SELECTION EXAMPLE: XCCLLHNAI

(L) (H) (N)

L	H	1000 - 4000 psi 25 psi (70 - 280 bar 1.1 bar), 3000 psi (210 bar)	N
	A	1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar), 3000 psi (210 bar)	V
	B	400 - 1500 psi 4 psi (28 - 105 bar 0.3 bar), 1000 psi (70 bar)	
	I	400 - 1500 psi 25 psi (28 - 105 bar 1.7 bar), 1000 psi (70 bar)	

PRIMARY CARTRIDGE

(A)

A	3:1 (with CBCA primary cartridge, 3:1,)
B	1.5:1 (with CBCBX primary cartridge, 1.5:1,)
G	4.5:1 (with CBCGX primary cartridge, 4.5:1,)
A	3:1 (with CBCAX primary cartridge, 3:1,)
G	4.5:1 (with CBCG primary cartridge, 4.5:1,)
B	1.5:1 (with CBCB primary cartridge, 1.5:1,)

INCLUDED COMPONENTS

Part	Description	Quantity
CBCALHN	Cartridge - Primary	2
CXDAXCN	Cartridge	2
FMDFMDN	Cartridge	2