



This cavity plug blocks all ports.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-16A
Series	3
Maximum Operating Pressure	5000 psi
Port Configuration	2 Port
Valve Hex Size	1 1/4 in.
Valve Installation Torque	150 - 160 lbf ft
Seal kit - Cartridge	Buna: 990-016-007
Seal kit - Cartridge	EPDM: 990-016-014
Seal kit - Cartridge	Polyurethane: 990-016-002
Seal kit - Cartridge	Viton: 990-016-006

OPTION SELECTION EXAMPLE: XICAXXNV

CONTROL	(X)	ADJUSTMENT RANGE	(X)	SEAL MATERIAL	(V)	MATERIAL/COATING
X -		X -		V Viton		Standard Material/Coating
				E EPDM		/AP Stainless Steel, Passivated
				N Buna-N		/LH Mild Steel, Zinc-Nickel

TECHNICAL FEATURES

- Cartridges configured with EPDM seals are for use in systems with phosphate ester fluids. Exposure to petroleum based fluids, greases and lubricants will damage the seals.
- Corrosion resistant cavity plugs are intended for use in corrosive environments and are identified by the model code suffix /AP (see CONFIGURATION section). The bodies of these plugs are made from high strength lean duplex stainless steel. Internal parts are made from carbon steel leaded alloy, the same as standard plugs.