



These cavity plugs can be used for both four-port and six-port cavities. When used in four-port cavities (T-21A, T-22A, T-23A and T-24A), ports 1 and 2 remain connected and ports 3 and 4 are blocked. When used in six-port cavities (T-61A, T-62A, T-63A and T-64A), ports 1, 2, 3 and 4 remain connected and ports 5 and 6 are blocked.

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                            |                           |
|----------------------------|---------------------------|
| Cavity                     | T-22A & T-62A             |
| Series                     | 2                         |
| Maximum Operating Pressure | 5000 psi                  |
| Valve Hex Size             | 1 1/8 in.                 |
| Valve Installation Torque  | 45 - 50 lbf ft            |
| Seal kit - Cartridge       | Buna: 990-022-007         |
| Seal kit - Cartridge       | Polyurethane: 990-022-002 |
| Seal kit - Cartridge       | Viton: 990-022-006        |

## OPTION SELECTION EXAMPLE: XNOAXXNV

---

| CONTROL | (X) ADJUSTMENT RANGE | (X) SEAL MATERIAL (N) |
|---------|----------------------|-----------------------|
| X -     | X -                  | N Buna-N<br>V Viton   |