





Accumulator sense, pump unload assembly with flow control valve

CAPACITY: 15 gpm



sunhydraulics.com/model/XQCJ





This valve assembly is meant to charge an accumulator using a fixed displacement pump. It incorporates a ventable priority flow control valve. When the pressure reaches the set point of the valve, the priority flow control is vented and all of the pump flow is available to the system. When the pressure drops to the value determined by the fixed percentage of the pilot valve, the priority flow is used to recharge the accumulator. Only the priority flow is directed to the accumulator leaving the rest of the pump flow available to the system. The assembly has two additional features; a simple circuit that softens the unloading of the pump and a system over-pressure relief.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	Line mount
Mounting Hole Quantity	2

NOTES: • *Important:* Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

• For detailed information regarding the cartridges contained in this assembly, click on the models codes shown in the Included Components tab.

2024 Sun Hydraulics 1 of 2





Accumulator sense, pump unload assembly with flow control valve

CAPACITY: 15 gpm

Continued from previous page

CONFIGURATION OPTIONS

Model Code Example: XQCJLANBK

CONTROL (L) ADJUSTMENT RANGE (A) SEAL MATERIAL (N)

Standard Screw Adjustment

1000 - 3000 psi (70 - 210 bar), 1000 psi (70 bar) Standard Setting

N Buna-N V Viton

PRIMARY CARTRIDGE

(B)

В	20% (with QCDB primary cartridge, 20%, accumulator sense, pump unload valve with check - pilot capacity)
E	10% (with QCDE primary cartridge, 10%, accumulator sense, pump unload valve with check - pilot capacity)
D	50% (with QCDD primary cartridge, 50%, accumulator sense, pump unload valve with check - pilot capacity)
С	30% (with QCDC primary cartridge, 30%, accumulator sense, pump unload valve with check - pilot capacity)
Α	15% (with QCDA primary cartridge, 15%, accumulator sense, pump unload valve with check - pilot capacity)

INCLUDED COMPONENTS

Part	Description	Quantity
A330-006-004*	SAE Plug	1
A330-006-006*	SAE Plug	1
A330-006-012*	SAE Plug	1
FVCAXAN	Cartridge	1
LPBDXDN	Cartridge	1
QCDBLAN	Cartridge - Primary	1
RDDFXBN	Cartridge	1

©2024 Sun Hydraulics 2 of 2