



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	.2 - 6 gpm
	2

**CONFIGURATION OPTIONS**

**Model Code Example: XQCKLANBK**

(L)

(A)

(N)

<b>L</b>	<b>A</b>	1000 - 3000 psi (70 - 210 bar), 1000 psi (70 bar)	<b>N</b>
<b>C</b>			<b>V</b>

**PRIMARY CARTRIDGE**

(B)

<b>B</b>	20% (with QCDB primary cartridge, 20%,	-	)
<b>E</b>	10% (with QCDE primary cartridge, 10%,	-	)
<b>D</b>	50% (with QCDD primary cartridge, 50%,	-	)
<b>C</b>	30% (with QCDC primary cartridge, 30%,	-	)
<b>A</b>	15% (with QCDA primary cartridge, 15%,	-	)

**INCLUDED COMPONENTS**

Part	Description	Quantity
A330-006-004*	SAE Plug	1
A330-006-006*	SAE Plug	1
A330-006-012*	SAE Plug	1
COFOXDN	Cartridge	1
FVCAXAN	Cartridge	1
LPBDXDN	Cartridge	1
QCDBLAN	Cartridge - Primary	1
RDDFXAN	Cartridge	1