



**TECHNICAL DATA**

		NOTE: DATA MAY VARY BY
	160 L/min.	

**CONFIGURATION**

<b>L</b>	
<b>A</b>	1000 - 3000 psi (70 - 210 bar), 1000 psi (70 bar)
<b>N</b>	
<b>B</b>	Pilot Ratio (4th Letter) of Primary Cartridge 20% (with QPAB primary cartridge, 20%, , - )
<b>N</b>	Port and Material Designation Ports P, T, & SYS 1 — SAE 20; Port SYS 2 — SAE 16; Port G — SAE 6; Port D — SAE 6; Aluminum

CONFIGURATION. SEE CONFIGURATION SECTION.

**OPTION SELECTION EXAMPLE: XQGELANBN**

(L) (A) (N)

<b>L</b>	<b>A</b> 1000 - 3000 psi (70 - 210 bar), 1000 psi (70 bar)	<b>N</b> V
----------	------------------------------------------------------------	---------------

**PRIMARY CARTRIDGE (B)**

<b>B</b>	20% (with QPAB primary cartridge, 20%, , - )
<b>D</b>	50% (with QPAD primary cartridge, 50%, , - )
<b>C</b>	30% (with QPAC primary cartridge, 30%, , - )
<b>A</b>	15% (with QPAA primary cartridge, 15%, , - )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CXHAXCN	Cartridge	1
QPABLAN	Cartridge - Primary	1
RVGFXAN	Cartridge	1