

OPTION SELECTION EXAMPLE: XQGFLANBN

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
L Standard Screw Adjustment	A 1000 - 3000 psi (70 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N	
C Tamper Resistant - Factory Set		V Viton	

PRIMARY CARTRIDGE (B)

B 20% (with QPAB primary cartridge, 20%, accumulator sense, pump unload valve - pilot capacity)
E 10% (with QPAE primary cartridge, 10%, accumulator sense, pump unload valve - pilot capacity)
D 50% (with QPAD primary cartridge, 50%, accumulator sense, pump unload valve - pilot capacity)
C 30% (with QPAC primary cartridge, 30%, accumulator sense, pump unload valve - pilot capacity)
A 15% (with QPAA primary cartridge, 15%, accumulator sense, pump unload valve - pilot capacity)

INCLUDED COMPONENTS

Part	Description	Quantity
A330-006-006*	SAE Plug	1
A330-006-012*	SAE Plug	1
CXHAXCN	Cartridge	1
LPBDXFN	Cartridge	1
QPABLAN	Cartridge - Primary	1
RVGFXAN	Cartridge	1