



## TECHNICAL DATA

Body Type	Line mount
Mounting Hole Thread	.375-16 UNC - 2B in.
Mounting Hole Depth	22,4 mm
Mounting Hole Quantity	3

**OPTION SELECTION EXAMPLE: XQGFLANBN**

CONTROL		(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
<b>L</b>	Standard Screw Adjustment	<b>A</b> 1000 - 3000 psi (70 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	<b>V</b> Viton
<b>C</b>	Tamper Resistant - Factory Set			
PRIMARY CARTRIDGE				(B)
<b>B</b>	20% (with QPAB primary cartridge, 20%, detector de presión en el acumulador, descargador de bomba válvula - capacidad de pilotaje)			
<b>E</b>	10% (with QPAE primary cartridge, 10%, detector de presión en el acumulador, descargador de bomba válvula - capacidad de pilotaje)			
<b>D</b>	50% (with QPAD primary cartridge, 50%, detector de presión en el acumulador, descargador de bomba válvula - capacidad de pilotaje)			
<b>C</b>	30% (with QPAC primary cartridge, 30%, detector de presión en el acumulador, descargador de bomba válvula - capacidad de pilotaje)			
<b>A</b>	15% (with QPAA primary cartridge, 15%, detector de presión en el acumulador, descargador de bomba válvula - capacidad de pilotaje)			

**INCLUDED COMPONENTS**

Part	Description	Quantity
A330-006-006*	SAE Plug	1
A330-006-012*	SAE Plug	1
CXHAXCN	Cartridge	1
LPBDXFN	Cartridge	1
QPABLAN	Cartridge - Primary	1
RVGFXAN	Cartridge	1