



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	montaje en línea
Control Flow Range	1 - 200 L/min.
Mounting Hole Thread	.375-16 UNC - 2B in.
Mounting Hole Depth	22,4 mm
Mounting Hole Quantity	3

**CONFIGURATION OPTIONS**

**Model Code Example: XQILLANBN**

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
<b>L</b> Standard Screw Adjustment	<b>A</b> 1000 - 3000 psi (70 - 210 bar), 1000 psi (70 bar) Standard Setting	<b>N</b> Buna-N	
<b>C</b> Tamper Resistant - Factory Set		<b>V</b> Viton	
<b>K</b> manilla			

**PRIMARY CARTRIDGE**

(B)

<b>B</b> 20% (with QPAB primary cartridge, 20%, detector de presión en el acumulador, descargador de bomba válvula - capacidad de pilotaje)
<b>E</b> 10% (with QPAE primary cartridge, 10%, detector de presión en el acumulador, descargador de bomba válvula - capacidad de pilotaje)
<b>D</b> 50% (with QPAD primary cartridge, 50%, detector de presión en el acumulador, descargador de bomba válvula - capacidad de pilotaje)
<b>C</b> 30% (with QPAC primary cartridge, 30%, detector de presión en el acumulador, descargador de bomba válvula - capacidad de pilotaje)
<b>A</b> 15% (with QPAA primary cartridge, 15%, detector de presión en el acumulador, descargador de bomba válvula - capacidad de pilotaje)

**INCLUDED COMPONENTS**

Part	Description	Quantity
A330-006-006*	SAE Plug	2
A330-006-012*	SAE Plug	1
CXHAXCN	Cartridge	1
FVFAXAN	Cartridge	1
LPBDXDN	Cartridge	1
QPABLAN	Cartridge - Primary	1
RDJFXAN	Cartridge	1
XZCCXXN	Cartridge	1
XZOCXXN	Cartridge	1