



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|--|------------|
| | |
| | 120 L/min. |
| | 10,7 mm |
| | Through |
| | 2 |

OPTION SELECTION EXAMPLE: XRELLANFM

| (L) | (A) | (N) |
|----------|---|----------|
| L | A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) | N |
| C | | V |
| W | B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) | |
| Y | C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar) | |
| | D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) | |
| | E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) | |
| | N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar) | |
| | Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar) | |
| | W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) | |

INCLUDED COMPONENTS

| Part | Description | Quantity |
|---------|---------------------|----------|
| CSABXXN | Cartridge | 1 |
| DTAFMHN | Cartridge | 1 |
| RVEALAN | Cartridge - Primary | 2 |

TECHNICAL FEATURES

- FLeX