



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	480 L/min.
	4

OPTION SELECTION EXAMPLE: XRGOLAN6

(L)	(A)	(N)	PORT AND MATERIAL DESIGNATION(6)
L	<p>A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)</p> <p>Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)</p>	N V	<p>6 Ports 1 & 2 — 1 1/2" Code 62 ; Port T — SAE 16; Gage Ports — SAE 6; Mtg Holes — .375 - 16UNC x .88 DP; Aluminum</p> <p>6/M Ports 1 & 2 — 1 1/2" Code 62 ; Port T — 1" BSPP; Gage Ports — 1/4" BSPP; Mtg Holes — M10 x 1.5-6H x .88 DP; Metric Aluminum</p> <p>6/S Ports 1 & 2 — 1 1/2" Code 62 ; Port T — SAE 16; Gage Ports — SAE 6; Mtg Holes — .375 - 16UNC x .88 DP; Iron</p> <p>6/T Ports 1 & 2 — 1 1/2" Code 62 ; Port T — 1" BSPP; Gage Ports — 1/4" BSPP; Mtg Holes — M10 x 1.5-6H x .88 DP; Metric Iron</p>