



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                        |                  |
|------------------------|------------------|
| Body Type              | montaje en línea |
| Interface              | 1.50 SAE C61     |
| Mounting Hole Quantity | 2                |

**CONFIGURATION OPTIONS**

**Model Code Example: XRIALANFR224**

| CONTROL  | (L)                            | ADJUSTMENT RANGE | (A)   | SEAL MATERIAL | (N)    |
|----------|--------------------------------|------------------|---|---------------|--------|
| <b>L</b> | Standard Screw Adjustment      | <b>A</b>         | 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar) Standard Setting    | <b>N</b>      | Buna-N |
| <b>C</b> | Tamper Resistant - Factory Set | <b>B</b>         | 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar) Standard Setting   | <b>V</b>      | Viton  |
| <b>K</b> | manilla                        | <b>D</b>         | 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting      |               |        |
|          |                                | <b>E</b>         | 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting      |               |        |
|          |                                | <b>W</b>         | 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar) Standard Setting |               |        |

**INCLUDED COMPONENTS**

| Part       | Description         | Quantity |
|------------|---------------------|----------|
| DTAFMHN224 | Cartridge           | 1        |
| RVIALAN    | Cartridge - Primary | 1        |