



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

--	--

CONFIGURATION OPTIONS

Model Code Example: XRJCLANAM

(L)	(A)	(N)
L	A 100 - 3000 psi (7 - 210 bar), 1000 psi (70 bar)	N
C		V
W	B 50 - 1500 psi (3,5 - 105 bar), 1000 psi (70 bar)	
Y	C 150 - 6000 psi (10,5 - 420 bar), 1000 psi (70 bar)	
	D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar)	
	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar)	
	N 60 - 800 psi (4 - 55 bar), 400 psi (28 bar)	
	Q 60 - 400 psi (4 - 28 bar), 200 psi (14 bar)	
	W 150 - 4500 psi (10,5 - 315 bar), 1000 psi (70 bar)	

PRIMARY CARTRIDGE

(A)

A	A (with RPIC primary cartridge, Pilot-operated,)
A	A (with RPIC8 primary cartridge, Pilot-operated, T-8A)

INCLUDED COMPONENTS

Part	Description	Quantity
DSIHXHN	Cartridge	1
RPICLAN	Cartridge - Primary	1