



TECHNICAL DATA

Body Type	Line mount
Capacity	1 L/min.
Mounting Hole Diameter	7,1 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2

OPTION SELECTION EXAMPLE: YCAALANCJ

CONTROL	(L) ADJUSTMENT RANGE	(A) SEAL MATERIAL	(N)
L Standard Screw Adjustment	A 25 - 3000 psi (1,7 - 210 bar), 1000 psi (70 bar) Standard Setting	N Buna-N	
C Tamper Resistant - Factory Set	B 25 - 1500 psi (1,7 - 105 bar), 1000 psi (70 bar) Standard Setting	V Viton	
F Hex Head Screw with Locknut	C 25 - 6000 psi (1,7 - 420 bar), 1000 psi (70 bar) Standard Setting		
W Hex Wrench Adjustment	D 25 - 800 psi (1,7 - 55 bar), 400 psi (28 bar) Standard Setting		
Y manilla de tres agarres	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting		
	W 25 - 4500 psi (1,7 - 315 bar), 1000 psi (70 bar) Standard Setting		

PRIMARY CARTRIDGE (C)

C 30 psi (2 bar) (with RBAC primary cartridge, Acción-directa alivio válvula - capacidad de pilotaje)
A 4 psi (0,3 bar) (with RBAC primary cartridge, Acción-directa alivio válvula - capacidad de pilotaje)
B 15 psi (1 bar) (with RBAC primary cartridge, Acción-directa alivio válvula - capacidad de pilotaje)
D 50 psi (3,5 bar) (with RBAC primary cartridge, Acción-directa alivio válvula - capacidad de pilotaje)
E 75 psi (5 bar) (with RBAC primary cartridge, Acción-directa alivio válvula - capacidad de pilotaje)
F 100 psi (7 bar) (with RBAC primary cartridge, Acción-directa alivio válvula - capacidad de pilotaje)
Z 1 psi (0,07 bar) (with RBAC primary cartridge, Acción-directa alivio válvula - capacidad de pilotaje)

INCLUDED COMPONENTS

Part	Description	Quantity
CXDAXCN	Cartridge	1
RBACLAN	Cartridge - Primary	1