



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Body Type	montaje en línea
Mounting Hole Diameter	10,7 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2

CONFIGURATION OPTIONS

Model Code Example: YCBILHNAJ

CONTROL	(L) FUNCTIONAL SETTING RANGE	(H) SEAL MATERIAL	(N)
L Standard Screw Adjustment	H 1000 - 4000 psi w/25 psi Check (70 - 280 bar w/ 1,7 bar Check), 3000 psi (210 bar) Standard Setting	N Buna-N	
C Tamper Resistant - Factory Set	A 1000 - 4000 psi w/4 psi Check (70 - 280 bar w/ 0,3 bar Check), 3000 psi (210 bar) Standard Setting	V Viton	
	B 400 - 1500 psi w/4 psi Check (28 - 105 bar w/ 0,3 bar Check), 1000 psi (70 bar) Standard Setting		

PRIMARY CARTRIDGE

(A)

A	3:1 (with CBBA primary cartridge, Proporción de pilotaje 3:1 , restrictiva contrabalance válvula)
H	10:1 (with CBBHX primary cartridge, Ajuste fijo, proporción de pilotaje 10:1 , restrictiva contrabalance válvula)
G	4.5:1 (with CBBGX primary cartridge, Ajuste fijo, proporción de pilotaje 4.5:1 , restrictiva contrabalance válvula)
A	3:1 (with CBBAX primary cartridge, Ajuste fijo, proporción de pilotaje 3:1 , restrictiva contrabalance válvula)
H	10:1 (with CBBH primary cartridge, Proporción de pilotaje 10:1 , restrictiva contrabalance válvula)
G	4.5:1 (with CBBG primary cartridge, Proporción de pilotaje 4.5:1 , restrictiva contrabalance válvula)

INCLUDED COMPONENTS

Part	Description	Quantity
CBBALHN	Cartridge - Primary	4
CXCDXCN	Cartridge	4
FSBDXAN	Cartridge	2