



**CONFIGURATION OPTIONS**

**Model Code Example: YCBILINAJ**

CONTROL	(L) FUNCTIONAL SETTING RANGE	(I) SEAL MATERIAL	(N)
L Standard Screw Adjustment	I 400 - 1500 psi w/25 psi Check (28 - 105 bar w/ 1,7 bar Check), 1000 psi (70 bar) Standard Setting	N Buna-N	
C Tamper Resistant - Factory Set		V Viton	

**PRIMARY CARTRIDGE**

(A)

A	3:1 (with CBBA primary cartridge, Proporción de pilotaje 3:1 , restrictiva contrabalance válvula )
H	10:1 (with CBBHX primary cartridge, Ajuste fijo, proporción de pilotaje 10:1 , restrictiva contrabalance válvula )
G	4.5:1 (with CBBGX primary cartridge, Ajuste fijo, proporción de pilotaje 4.5:1 , restrictiva contrabalance válvula )
A	3:1 (with CBBAX primary cartridge, Ajuste fijo, proporción de pilotaje 3:1 , restrictiva contrabalance válvula )
H	10:1 (with CBBH primary cartridge, Proporción de pilotaje 10:1 , restrictiva contrabalance válvula )
G	4.5:1 (with CBBG primary cartridge, Proporción de pilotaje 4.5:1 , restrictiva contrabalance válvula )

**INCLUDED COMPONENTS**

Part	Description	Quantity
CBBALIN	Cartridge - Primary	4
CXCDXCN	Cartridge	4
FSBDXAN	Cartridge	2