



TECHNICAL DATA

Body Type	Line mount
Capacity	2,5 - 12 L/min.
Mounting Hole Diameter	10,7 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2

OPTION SELECTION EXAMPLE: YCBILINAJ

CONTROL		(L) FUNCTIONAL SETTING RANGE	(I) SEAL MATERIAL	(N)
L	Standard Screw Adjustment	I 400 - 1500 psi w/25 psi Check (28 - 105 bar w/ 1,7 bar Check), 1000 psi (70 bar) Standard Setting	N	Buna-N
C	Tamper Resistant - Factory Set		V	Viton

PRIMARY CARTRIDGE (A)

A	3:1 (with CBBA primary cartridge, Proporción de pilotaje 3:1 , restrictiva contrabalance válvula)
H	10:1 (with CBBHX primary cartridge, Ajuste fijo, proporción de pilotaje 10:1 , restrictiva contrabalance válvula)
G	4.5:1 (with CBBGX primary cartridge, Ajuste fijo, proporción de pilotaje 4.5:1 , restrictiva contrabalance válvula)
A	3:1 (with CBBAX primary cartridge, Ajuste fijo, proporción de pilotaje 3:1 , restrictiva contrabalance válvula)
H	10:1 (with CBBH primary cartridge, Proporción de pilotaje 10:1 , restrictiva contrabalance válvula)
G	4.5:1 (with CBBG primary cartridge, Proporción de pilotaje 4.5:1 , restrictiva contrabalance válvula)

INCLUDED COMPONENTS

Part	Description	Quantity
CBBALIN	Cartridge - Primary	4
CXCDXCN	Cartridge	4
FSBDXAN	Cartridge	2