



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|                        |            |
|------------------------|------------|
| Body Type              | Line mount |
| Mounting Hole Diameter | .28 in.    |
| Mounting Hole Depth    | Through    |
| Mounting Hole Quantity | 2          |

- NOTES:**
- **Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.
  - For detailed information regarding the cartridges contained in this assembly, click on the models codes shown in the Included Components tab.

**CONFIGURATION OPTIONS**

Model Code Example: YCCAXCNAJ

| CONTROL                 | (X) CRACKING PRESSURE   | (C) SEAL MATERIAL | (N) |
|-------------------------|-------------------------|-------------------|-----|
| <b>X</b> Standard Pilot | <b>C</b> 30 psi (2 bar) | <b>N</b> Buna-N   |     |
|                         | D 50 psi (3,5 bar)      | V Viton           |     |
|                         | E 75 psi (5 bar)        |                   |     |
|                         | F 100 psi (7 bar)       |                   |     |

**PRIMARY CARTRIDGE**

(A)

|          |   |
|----------|---|
| <b>A</b> | A (with CKCB primary cartridge, Pilot-to-open check valve with standard pilot)  |
| A        | A (with CKCBV primary cartridge, Vented pilot-to-open check valve with 1/4 NPTF external pilot port and standard pilot) |
| A        | A (with CKCBS primary cartridge, Vented pilot-to-open check valve with SAE-4 external pilot port and standard pilot)    |

**INCLUDED COMPONENTS**

| Part    | Description         | Quantity |
|---------|---------------------|----------|
| CKCBXCN | Cartridge - Primary | 2        |
| RPECJAN | Cartridge           | 2        |