



TECHNICAL DATA

Body Type	Line mount
Capacity	6 - 30 L/min.
Mounting Hole Diameter	10,7 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2

OPTION SELECTION EXAMPLE: YCCILINAJ

CONTROL		(L) FUNCTIONAL SETTING RANGE	(I) SEAL MATERIAL	(N)
L	Standard Screw Adjustment	I 400 - 1500 psi w/25 psi Check (28 - 105 bar w/ 1,7 bar Check), 1000 psi (70 bar) Standard Setting	N	Buna-N
C	Tamper Resistant - Factory Set		V	Viton

PRIMARY CARTRIDGE		(A)
A	3:1 (with CBCA primary cartridge, Proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula)	
H	10:1 (with CBCHX primary cartridge, Ajuste fijo, proporción de pilotaje 10:1 , capacidad estándar contrabalance válvula)	
G	4.5:1 (with CBCGX primary cartridge, Ajuste fijo, proporción de pilotaje 4.5:1 , capacidad estándar contrabalance válvula)	
A	3:1 (with CBCAX primary cartridge, Ajuste fijo, proporción de pilotaje 3:1 , capacidad estándar contrabalance válvula)	
H	10:1 (with CBCH primary cartridge, Proporción de pilotaje 10:1 , capacidad estándar contrabalance válvula)	
G	4.5:1 (with CBCG primary cartridge, Proporción de pilotaje 4.5:1 , capacidad estándar contrabalance válvula)	

INCLUDED COMPONENTS

Part	Description	Quantity
CBCALIN	Cartridge - Primary	4
CXCDXCN	Cartridge	4
FSCDXAN	Cartridge	2