



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	8.6 mm
	Through
	2

CONFIGURATION OPTIONS

Model Code Example: YCCSLHNAK

	(L)	(H)	(N)
L		H 1000 - 4000 psi 25 psi (70 - 280 bar 1.1), 3000 psi (210 bar)	N
C	-	A 1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar), 3000 psi (210 bar)	V
		B 400 - 1500 psi 4 psi (28 - 105 bar 0.3 bar), 1000 psi (70 bar)	
		I 400 - 1500 psi 25 psi (28 - 105 bar 1.7 bar), 1000 psi (70 bar)	

PRIMARY CARTRIDGE

(A)

A	3:1 (with CBCA primary cartridge, 3:1,)
H	10:1 (with CBCHX primary cartridge, 10:1,)
G	4.5:1 (with CBCGX primary cartridge, 4.5:1,)
A	3:1 (with CBCAX primary cartridge, 3:1,)
H	10:1 (with CBCH primary cartridge, 10:1,)
G	4.5:1 (with CBCG primary cartridge, 4.5:1,)

INCLUDED COMPONENTS

Part	Description	Quantity
260-010*	Seat	1
340-002*	Pipe Plug	1
800-001-070*	Ball	1
CBCALHN	Cartridge - Primary	2
CXCDXCN	Cartridge	2